

TECHNICAL DATA

CHASSIS

Suspension	Leaf suspension (front axle)
Option:	<i>Air suspension (rear axle)</i>
Axles	2
Underride protection	rear
Colour	black
Exterior lighting	LED
Side marker lamps	LED
Brakes	Air brake system
FA	Disc brake
RA	Drum brake
Safety	ABS, ASR, ESP, AEBS
Tyres	275/80 R22.5
Option:	<i>295/80 R22.5</i>

BATTERY

Battery type	Lithium-ion / LFP
Battery capacity	250 kWh
Battery voltage	540.96 V
Battery charge	DC 120 kW AC 22 kW

ZERO EMISSION  **100% ELECTRIC**



VS6

FULL-ELECTRIC SWEEPER

ZERO EMISSION  **100% ELECTRIC**




**EXPERIENCE LIVE NOW
ASK FOR AN APPOINTMENT!**



BROCK Kehrtechnik GmbH
Arnoldschacht 14
D-44894 Bochum

Tel.: +49 234 - 911 74 - 0
Fax: +49 234 - 911 74 - 293
E-mail: sales@brock-kehrtechnik.de

WWW.BROCK-KEHRTECHNIK.DE



BROCK
MEMBER OF FOTON MOTOR

VS6e

ZERO EMISSION  100% ELECTRIC


THE VISION COMES TRUE!
The perfect all-electric sweeping machine for cities and municipalities.

The NEW GENERATION BROCK VS6e is the symbiosis of a powerful FOTON 16.250 S chassis and the proven BROCK VS6e tradition.

Combine proven battery technology from a renowned supplier and the manufacturing expertise of one of the world's largest chassis manufacturers with the market knowledge of a leading sweeping machine manufacturer, and the result is a world-class sweeper - the future vision for sustainable and thorough urban cleaning.

The full-electric drive not only ensures thorough cleaning and clean streets, but also protects the environment with low noise levels and **CO₂ emissions of 0%**. Thanks to the optimised fan technology, the machine achieves the same performance and is **low-maintenance** compared to a conventional sweeper with an auxiliary engine.

The VS6e is equipped with a **digital control panel** to make it as comfortable as possible for the driver. Less vibration and the generally quieter driving style also contribute to a **reduction in stress and wear**.



6 m³ 1,500 l



2.600 mm to 3.850mm



EQUIPMENT

DEBRIS HOPPER 6 m³

with round hopper base, integrated 1,500 l water tank
Debris hopper and water tank made of stainless steel (1.4301), outer cladding made of GRP

SWEEPING WIDTH

2.600 mm to 3.850 mm

SWEEPING SYSTEM RIGHT, + LEFT (OPTION) with a pushed rotary brush

- Two-speed coarse pick-up
- Rotary brush retractable and extendable in sweep mode
- Sweeper unit extendable and retractable in sweep mode
- Working lights in LED version
- Infinitely adjustable speed of the brush
- **Simultaneous work** with both sweeping-suction units
- **Swivelling cylindrical roller brush**

INSPECTION DOOR

Right incl. step and grab rail

MINI CONTROL PANEL

in the door with CAN bus control

SUCTION HOSE UNIT

pneumatically supported on the tailgate

HIGH-PRESSURE CLEANER

150 bar, 15 l incl. hose drum, spraying handgun with lance, hose length 15 m

WATER BAR on front, low-pressure

